



Product Line Card

Product Number	Product Description	
35	EPOXY, INJECTION ADHESIVES	2:1, High Modulus, 1:1 Low Modulus
100	EPOXY, SEMI-SELF LEVELING FLOOR COATING	STANDARD COLORS - CR & LT versions available
102	EPOXY, LOW VISCOSITY, BROADCAST / SEALER	GRAY
110	EPOXY, PIN RAKE APPLIED SURFACER, 60-100 MIL	GRAY, TILE RED
133	EPOXY BROADCAST BASECOAT	CLEAR
133	EPOXY TOPCOAT - CLEAR	CLEAR
133 Coving	EPOXY COVING MORTAR FOR 133 DECORATIVE COVING SYSTEM	Colorquartz
140 HS	HIGH SOLIDS URETHANE COATING SYSTEM, SOLVENT BASED	GRAY, CLEAR, BRIGHT WHITE
150	FIBER REINFORCED, EPOXY COATING SYSTEM	STANDARD COLORS - TFE, CR, HT & LT versions available.
160	EPOXY, BLOCK AND BUG HOLE FILLER	GRAY
230	EPOXY, SLURRY LINING SYSTEM, 40-60 mils.	GREY
260	1/8"EPOXY, TROWEL APPLIED LINER	CHARCOAL - CR, HT & LT versions available.
300 Coving	1/8" EPOXY VERTICAL COVING / RESURFACER	GRAY, TILE RED
300 Flex	FLEXIBLE EPOXY EXPANSION JOINT SEALER / FLEXIBLE MEMBRANE	STANDARD COLORS, CLEAR
301	PENETRATING EPOXY SEALER, ULTRA-LOW VISCOSITY	CLEAR
310	1/8" EPOXY SLURRY / BROADCAST - Moderate Skid Resistance	GRAY, TILE RED - CR version available.
330	STANDARD EPOXY PRIMER - 330, 330 AR, 330 CR, 330 PT, & 350 GROUT.	CLEAR - LT version available.
330	1/4" EPOXY, TROWEL APPLIED MORTAR - Primer Required	GRAY, TILE RED - AR, CR, HT, LT & PT versions available.
330 Patch Kit	1/4" EPOXY, TROWEL APPLIED MORTAR - PATCH KIT	GRAY & TILE RED - CR, LT & FAST CURE versions available.
335	1/4" EPOXY, TROWEL APPLIED SURFACER	GRAY & TILE RED - CR, LT & FAST CURE versions available.
340	1/4" EPOXY, SCREED / PIN RAKE APPLIED SURFACER - Topcoat Recommended	NATURAL, GRAY, TILE RED - CR version available.
350	EPOXY GROUT, TROWEL APPLIED - 1/4" - 1.25"	NATURAL - LT version available.
360 Tile Grout	EPOXY TILE GROUT / CRACK FILLER	GRAY, TILE RED - CR, HT & LT versions available.
370	EPOXY POURABLE GROUT	NATURAL - CR & LT versions available.
440	1/4" URETHANE SLURRY SURFACER - Thermal Shock Resistant - Topcoat Recommended	NATURAL, GRAY, TILE RED
500 / 600 Series	URETHANE, ONE COMPONENT, MOISTURE CURE CONCRETE SEALER	CLEAR
500	1/4" POLYESTER LAMINATE FLOORING SYSTEM	GRAY, TILE RED
550 Grout	POLYESTER TROWELABLE FILLER / PITCHING GROUT. Primer Required	NATURAL
600	1/4" VINYLESTER LAMINATE FLOORING SYSTEM	GRAY, TILE RED - Chlorendic & Novolac versions available.
640	VINYLESTER COATING SYSTEM - Heavy Duty	DARK GRAY, CHARCOAL - AR version available.
642	NOVOLAC VINYLESTER COATING SYSTEM - Heavy Duty	DARK GRAY, CHARCOAL - AR version available.
650	VINYLESTER COATING SYSTEM - Moderate Duty	GRAY, TILE RED - Chlorendic & Novolac versions available.
660 Coving	1/8" VINYLESTER, TROWEL APPLIED COVING	CHARCOAL - Chlorendic and Novolac versions available.
660 Liner	1/8" VINYLESTER, TROWEL APPLIED LINER	CHARCOAL - Chlorendic and Novolac versions available.
670	VINYLESTER POURABLE GROUT	NATURAL
700	WATER BASED EPOXY - VAPOR TRANSMISSION FLOOR COATING / SEALER	STANDARD COLORS - AR version available.
701	WATER BASED EPOXY- ULTRA LOW VISCOSITY PRIMER / SEALER	CLEAR
740	1/4" URETHANE MODIFIED EPOXY-PORTLAND CEMENT SLURRY - Thermal Shock Resistant	GRAY, NATURAL
810 AR	ABRASION RESISTANT CERAMIC FILLED BRUSHABLE COMPOSITE	GRAY
818 AR	ABRASION RESISTANT CERAMIC TOOL APPLIED COMPOSITE	GRAY
830 AR	ABRASION RESISTANT TROWEL APPLIED COMPOSITE - Primer Required	CHARCOAL
860 AR	1/8" ABRASION RESISTANT EPOXY, TROWEL APPLIED LINER	CHARCOAL - CR HT & LT versions available
870 AR	ABRASION RESISTENT EPOXY CASTABLE GROUT	CHARCOAL
Aggregates	SILICA, COLORQUARTZ, FILTER SANDS, PEA GRAVEL	NATURAL - Sizes to fit most needs

Coatings - Standard Color Availability - Gray, Light Gray, Dark Gray, Cream, Tan, Tile Red, Safety Yellow, Safety Blue, Safety Green
 CR - Chemical Resistant (Novolac), HT - High Temperature Resistant, LT - Low Temperature Cure, TFE - Surface Release Properties

GREENSTONE POLYMER SYSTEMS, INC.

400 Lombardi Avenue
 Green Bay, WI 54304

www.greenstonepolymer.com

Product Data Sheets are available on the web site.

Customer Service Team
 920-435-1548

